

## MAVERICK X3 X rc TURBO RR 72"

### HIGHLIGHTS

<b>DEFIANT</b>	<ul style="list-style-type: none"> <li>• Trademark Can-Am DNA with next-generation design</li> <li>• Low seating position</li> <li>• Ergo-Lok cockpit with four-way adjustable seats</li> </ul>
<b>POWERFUL</b>	<ul style="list-style-type: none"> <li>• Industry-leading 200 hp turbocharged and intercooled Rotax<sup>®</sup> ACE engine</li> <li>• Advanced airflow dynamics</li> <li>• QRS-X transmission</li> </ul>
<b>PRECISE</b>	<ul style="list-style-type: none"> <li>• TTX suspension with industry-leading travel</li> <li>• Ultra efficient and lightweight chassis</li> <li>• Sharpest handling features</li> </ul>
<b>PLATFORM FEATURES</b>	<ul style="list-style-type: none"> <li>• 72.8 in. (184.9 cm) wide</li> <li>• 102 in. (259.1 cm) wheelbase</li> <li>• 16 in. (40.6 cm) of ground clearance</li> <li>• High-torque Dynamic Power Steering (DPS™)</li> <li>• Up to 24 in. (61 cm) of suspension travel</li> <li>• Rear tow hook</li> </ul>
<b>SPECIFIC TO X rc TURBO RR 72" PACKAGE</b>	<ul style="list-style-type: none"> <li>• Belt-monitoring system</li> <li>• 200 hp Turbo RR engine</li> <li>• Smart-Lok™ front differential</li> <li>• FOX 3.0 PODIUM RC2 shocks with bypass</li> <li>• 15 in. (162.6 cm) aluminum beadlock wheels</li> <li>• 32 in. Maxxis Liberty tyres</li> <li>• Front bumper, half-doors, aluminum roof, intrusion bar</li> <li>• Front tow hook</li> <li>• HMWPE differential and under-bumper skid plates</li> <li>• HMWPE front and rear suspension arm</li> <li>• UHMWPE rock sliders</li> <li>• 4,500 lb (2,041 kg) winch with synthetic rope</li> <li>• 4-point harness with shoulder pads</li> <li>• X-package graphics/seats</li> <li>• 7.6 in. digital display with keypad</li> <li>• Can-Am LED signature</li> <li>• 850 W magneto</li> <li>• Painted color</li> </ul>



Chalk Gray & Magma Red / TURBO RR

### DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,843 lb (836 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

### FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skidplates: Full heavy-duty with differential/Under bumper/ Front and rear suspension arm Rear tow hook

### WARRANTY & SERVICE

Factory Warranty	2 years/15,000 km warranty, whichever comes first
------------------	---

ENGINE	TURBO RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)

### SUSPENSIONS

Front Suspension	Trophy truck-inspired arched double A-arm with sway bar/22 in. (55.9 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments

### TYRES & WHEELS

Front Tyres	Maxxis Liberty 32 x 10 x 15 in.
Rear Tyres	Maxxis Liberty 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

### BRAKES

Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers